

WATERTITE

Poly

WHITE OR GREY

TWO COMPONENT | CEMENT BASED | ELASTIC | WATERPROOFING



Waterproofing mix 20 kg dry mix + 10 kg liquid additive

DESCRIPTION:

TWO COMPONENTS, CEMENT BASED, ACRYLIC AND FIBER REINFORCED ELASTIC, GOOD LEVELING, UV RESISTANT, WATERPROOFING LAYER. FOR DECKS, BALCONIES, TERRACES.

PROVIDES WATERPROOF BASE FOR TILING APPLICATIONS

EFFECTIVE FOR POSITIVE SIDE WATERPROOFING

PRODUCT PREPARATION:

Mix two components (20 kg Dry Mix + 10 Kg Liquid additive) in a clean pail. Mix using low speed mechanical mixers to smooth throwable consistency.

Depending on the weather and application conditions, clean water can be added maximum of 10 %.

SURFACE PREPERATION:

Surfaces must be structurally sound, clean, dry, and free of dust, dirt or other contaminates impairing bond. Prepare the surface to be smooth and free of cracks, holes and voids.

APPLICATION:

Use trowel, squeegee or brush to apply the layers to be about 2–3 mm thickness (1/8 INCH) . Multiple coats in cross directional are recommended. Use quality fibermesh between coats for extra strenght.

CEMENT BASED SLURRY

2 PARTS DRY MIX 1 PART LIQUID ADDITIVE

COLOR: GREY / WHITE

OPEN TIME: 30 MINUTES

APPLICATION TEMPERATURE: 8– 30 C

DRY / CURE TIME: 7 DAYS AT 20– 30 C

COVERAGE:

Wet rooms: 2.5 – 3 kg / M2 (2 layers.)

Water tanks, pools and terraces: 3,5– 4 kg/m2 (2 layers)

STORAGE:

12 Months in dry condition in unopened packaging

GREY / WHITE





WATERTITE

Poly

WHITE OR GREY

TWO COMPONENT | CEMENT BASED | ELASTIC | WATERPROOFING



WARNING – HAZARDOUS MAY CAUSE IRRITATION

RISK: May cause respiratory, skin and eye irritation.

SAFETY: Avoid contact with the eyes and skin. Avoid inhaling the vapors and wear suitable protective clothing covering the skin including eye protection, gloves, and suitable respirators. Keep out of the reach of children.

FIRST AID: Flush eyes and wash skin thoroughly with clean water. If inhaled, vacate area immediately. Seek medical attention if irritation persists. If swallowed do not induce vomiting. Drink plenty of clean water and seek medical attention immediately.

SPILLS / LEAKS: Maintain work area and keep it clean. Keep out of sewers and storm drainage.

DISPOSAL: Follow above safety instructions and collect in disposal containers in accordance to local disposal requirements.

MANUAL HANDLING: The manual handling of this product without due care and attention could result in physical injury. Wear back supports and use team lifting when manual lifting is required. Follow all OSHA recommendations.

WARRANTY: KEMSET USA warrants this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product found to defective as purchased. In the event of a claim under this warranty, notice must be given to KEMSET USA in writing. This limited warranty is issued and accepted in lieu of other express warranties and expressly excludes liability for consequential

WARNING: This product contains impurities known to the State of California to cause cancer and / or birth defects or other reproductive harm

Keep out of the reach of children.



KEMSET USA
326 N. Avalon Blvd.
Wilmington, CA 90744
1(562) 285 2790

www.kemsetusa.com
sales@kemsetusa.com

CE
ISO9001 | Made in Turkey

Dry mix
20 kg ± 5%