

# THERMO PAINT

REPELS HEAT/COLD RADIATION

PROFESSIONAL



## LONG TERM PROTECTION

HELPS KEEP HOT OR COLD RADIATION AWAY FROM BUILDING EXTERIOR SURFACES  
REPELS HEAT OR COLD RADIATION.  
LOW HEAT OR COLD ABSORPTION AND RETENTION VALUE

### DESCRIPTION:

ACRYLIC WATERBASED EMULSION, RADIANT HEAT REPELLENT, HIGHLY ELASTIC, WATER-VAPOR PERMIABLE, WATER REPELLENT.

### SURFACE PREPARATION:

Surfaces must be structurally sound, clean, dry and free of dust, dirt or other contaminants impairing bond. Prepare the surface to be smooth and free of cracks, holes and voids.

### PRIME:


Apply even single coat of **KEMSET FLEX PRIMER** for better bonding. Allow primer to dry 4–6 hours before **THERMOPAINT** application.

### TYPES OF APPLICATIONS:

On smooth finished plasters, concrete surfaces, on EIFS systems as top coat, on exterior/ interior plasterboards, etc.

### APPLICATION:

Apply using brush or rollers. Maintain wet edge.



## RADIANT REFLECTIVE MICRO GLASS

### SPECIFICATIONS:

WATER BASED ACRYLIC  
MINERALS AND GLASS RADIANT PAINT  
COVERAGE: 1,20–1,35 kg/m<sup>2</sup> (1–1,5 mm thickness.)  
DRYING TIME: 12 hours  
FIRE CLASS: Bs1 ( EN 13501–1)  
NOT COMBUSTABLE  
BOND STRENGTH: 1,50 N/mm<sup>2</sup>  
SUN LIGHT Reflection: 65%  
HEAT RADIATION Transfer Rate: 63%



# THERMO PAINT

**WARNING – HAZARDOUS  
MAY CAUSE IRRITATION**

**RISK:** May cause respiratory, skin and eye irritation.

**SAFETY:** Avoid contact with the eyes and skin. Avoid inhaling the vapors and wear suitable protective clothing covering the skin including eye protection, gloves, and suitable respirators. Keep out of the reach of children.

**FIRST AID:** Flush eyes and wash skin thoroughly with clean water. If inhaled, vacate area immediately. Seek medical attention if irritation persists. If swallowed do not induce vomiting. Drink plenty of clean water and seek medical attention immediately.

**SPILLS / LEAKS:** Maintain work area and keep it clean. Keep out of sewers and storm drainage.

**DISPOSAL:** Follow above safety instructions and collect in disposal containers in accordance to local disposal requirements.

**MANUAL HANDLING:** The manual handling of this product without due care and attention could result in physical injury. Wear back supports and use team lifting when manual lifting is required. Follow all OSHA recommendations.

**ADDITIONAL INFORMATION / UPDATES:** Updated Material Safety Data Sheet ( MSDS ) and Product Data Sheet ( PDS ) are available at **KEMSET.COM**

**WARRANTY: KEMSET USA** warrants this product to be of merchantable quality when used or applied in accordance with the instructions herein. The product is not warranted as suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product found to defective as purchased. In the event of a claim under this warranty, notice must be given to **KEMSET USA** in writing. This limited warranty is issued and accepted in lieu of other express warranties and expressly excludes liability for consequential damages.

**WARNING:** This product contains impurities known to the State of California to cause cancer and / or birth defects or other reproductive harm

**Keep out of the reach of children.**



EN 1504-2



**KEMSET USA**  
326 N.Avalon Blvd.  
Wilmington, CA 90744

1(562) 285 2790

[www.kemsetusa.com](http://www.kemsetusa.com)  
[sales@kemsetusa.com](mailto:sales@kemsetusa.com)

**CE**  
ISO9001

**15 L**  
**(4 gal)**

± 5%

